



**WATER DOG™**  
The Ultimate Water Trailers



1-888 580-8330  
View the entire line  
of water trailers at:  
[www.ciequip.com](http://www.ciequip.com)

Turn your equipment trailer into a 1,635 gallon water trailer in minutes! Or you have the perfect static water source for your next project where there is no water. Built tough to withstand lifting, dragging or winching this unit can be loaded at a job site or yard with a backhoe, forklift, crane, front end loader etc.

This skid is totally self contained with 2" pump with 4.0 hp Honda gas engine, 2" steel piping, dual rear spray heads, hook-ups for 1 1/2" fire hose and garden hose, canal fill (self loading feature), hydrant fill, 18" manhole for top loading and cleaning. Ideal for dust control, the rear spray heads will spray up to 50' wide behind the trailer while it is towed. Water transport, fire control, ditch jetting, washing heavy equipment, street cleaning, watering riding and rodeo arenas, just a few of the many uses for this versatile skid.

## General Specifications

Capacity	..... 1,635 gallons
Dimensions,	length ..... 17' overall width ..... 74" height ..... 69"
Weight,	empty ..... 1,590 lbs loaded ..... 14,590 lbs
Frame,	inside cross members .... 4" x 4" steel tube double wide  outside rails ..... 6" channel with D rings for tie down; rails tapered at both ends for skidding or winching; lifting sling with lifting eye
Tank	..... polyethylene 3/8" thick elliptical leg tank 16" manhole for filling and cleaning baffles molded into sides of tank repairable and recyclable
Pump	..... Multiquip QP204H 2" centrifugal 4.0 hp Honda engine low oil shutdown, recoil start wrap-around frame for protection rated at 8,500 gph, 142 gpm



1-888 580-8330  
View the entire line  
of water trailers at:  
[www.ciequip.com](http://www.ciequip.com)

## General Specifications, continued

Pipe system	..... 2" steel pipe with special drain valves to prevent freezing 2" or 1½" fire hose hook-up with safety valve to prevent "water hammer" faucet for standard garden hose hook-up dual rear spray heads at the rear with replaceable caps control manifold controls all functions with five brass valves; simple to use numbered valves make operation a snap hydrant fill canal fill (drafting capability, self-loading)
Options	Hose reels, standard or rotating Side spray that fits on fire hose hook-up Multiquip high pressure pump, operating pressure 106 psi Remote controls (wire-operated) 12 volt system with 2" electrical valves make it possible to operate specific valves from the driver's location



1-888 580-8330

View the entire line  
of water trailers at:  
[www.ciequip.com](http://www.ciequip.com)

